

Reintera

Technical specifications

Print technology	Monochrome laser											
Print speed	Up to 14 ppm First page out: Less than 10 sec. due to Instant-on Technology (no warm-up time - from warm or cold start) Speed specification per industry standard testing methods											
Processor	234 MHz RISC processor											
Memory	2 MB											
Print quality	1200 dpi-like quality (600 dpi with REI and FastRes)											
Print languages	Host-based printing driver											
Economical printing levels	Economode (saves up to 50% toner at 600 dpi), immediate return to Powersave mode after each print job due to Instant-on Technology (saves electricity), N-up printing and manual two-sided printing - duplex (saves paper)											
Duty cycle	Up to 5,000 pages per month											
Print margins (mm)	Top: 4 mm, left: 4 mm, right: 4 mm, bottom: 4 mm											
Media handling	<table><thead><tr><th>Input</th><th>Capacity</th><th>Weight</th></tr></thead><tbody><tr><td>Main tray</td><td>Up to 150 sheets</td><td>60 g/m² to 163 g/m²</td></tr><tr><td>Priority tray</td><td>1 sheet</td><td>60 g/m² to 163 g/m²</td></tr></tbody></table>	Input	Capacity	Weight	Main tray	Up to 150 sheets	60 g/m ² to 163 g/m ²	Priority tray	1 sheet	60 g/m ² to 163 g/m ²		Size A4, A5, A6, B5, envelopes (C5, DL, B5), postcards 76 x 127 mm to 216 x 356 mm A4, A5, A6, B5, envelopes (C5, DL, B5), postcards 76 x 127 mm to 216 x 356 mm
Input	Capacity	Weight										
Main tray	Up to 150 sheets	60 g/m ² to 163 g/m ²										
Priority tray	1 sheet	60 g/m ² to 163 g/m ²										
Media types	Output: Sheets: up to 100, envelopes: 15, transparencies: 100 Duplex printing: Manual (driver support provided) Plain paper, envelopes, transparencies, cardstock, postcards, labels											
Interface and connectivity	Standard: 1 Hi-Speed USB (compatible with USB 2.0 specifications) port											
Operating systems compatibility	Microsoft® Windows® 98 SE, Me, 2000, XP 32-bit											
Minimum system requirements	Microsoft® Windows® 98 SE, Me, 2000 or XP, 90 MHz Pentium®, 120 MB free hard disk space (10 MB minimum install), CD-ROM drive, USB port (compatible with USB 2.0 specifications)											
Standard software	HP printer software on CD-ROM includes HP installer/uninstaller, host-based driver, HP toolbox for diagnostic status and configuration, help, documentation Driver downloadable: latest drivers available from the HP support website at http://www.hp.com/support											
Control panel	2 LED lights (Attention, Ready)											
Power	Requirements: Input voltage 110 to 127 VAC (± 10%), 50/60 Hz (± 2 Hz), 3.5 amps; 220 to 240 VAC (± 10%), 50/60 Hz (± 2 Hz), 2 amps Supply type: Internal Consumption*: Active: 250 watts, Off: 0 watts, Powersave: 2 watts, Standby: 2 watts *Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. Doing so might damage the printer and void the product warranty.											
Dimensions (w x d x h)	Out of package: 370 x 230 x 208 mm, packaged: 500 x 300 x 345 mm											
Weight	Out of package: 5 kg; packaged: 7.21 kg											
Printer management	HP Toolbox											
Operating environment	Environmental ranges: Operating temperature: 10 to 32.5° C, operating humidity: 20 to 80% RH, recommended operating humidity: 20 to 80% RH, recommended operating temperature: 10 to 32.5° C, storage temperature: 0 to 40° C, storage humidity: 10 to 80% RH, Noise level per ISO 9296: sound power LwAd: 6.2 B(A), Sound pressure: LpAm: 4.9 B(A)											
Certifications	CISPR 22: 1997/EN 55022: 1998 Class B, EN 61000-3-2: 2000, EN 61000-3-3: 1995+A1, EN 55024: 1998+A1, FCC Title 47 CFR, Part 15 Class B (USA), ICES-003, Issue 4, (Canada), GB9254-1998, EMC Directive 89/336/EEC with CE Marking Regulatory standards: IEC 60950-1 (International), EN 60950-1 (EU), IEC 60825-1+A1+A2, UL/cUL Listed (US/Canada), GS License (Europe), EN 60825-1+A1+A2 Class 1, 21 CFR Ch. I/SubCh J (Class 1 Laser/LED Device) GB4943.2001, Low Voltage Directive 73/23/EEC with CE Marking (Europe); other safety approvals as required by individual countries. Energy Star											
Warranty	One-year limited warranty											

LED Projector

without notice (last updated: March 2016)

Display	Technology:	0,55" DLP™ chip (XGA)
	Resolution:	1,024 x 768 pixels (XGA)
Illumination technology	Type:	Laser and LED hybrid technology
	Service life:	Up to 20,000 hours
Picture	Brightness:	2,700 AL
	Contrast:	20,000:1
Projection lens	Colour depth:	Up to 1.07 billion (full colour)
	Technology:	1,1x optical zoom
	Projection ratio:	(viewing distance: width): 1.54–1.71:1
	Offset:	72%
	Min. distance:	0.83 m
	Focus:	Manual
Projection	Size of the projection screen:	30" (0,76 m) to 300" (7,62 m)
	60" screen:	1.8 m to 2.0 m viewing distance
	100" screen:	3.1 m to 3.4 m viewing distance
Keystone correction	Vertical (manual):	+30°/±30°
Interfaces	Computer:	1 x 15-pin D-Sub (VGA)
	Digital input:	HDMI port
	Audio:	Input terminal: 3.5 mm stereo mini jack x1 Output terminal: 3.5 mm stereo mini jack x1 (variable audio input)
Extended functions	Control inputs:	RS-232C
	Other/further inputs:	Micro-USB type B; firmware update
Operating noise		Direct power on, direct power off, rear projection, freeze, blank screen, ceiling mounting, (4x M4), digital zoom (2x), presentation timer, password protection feature
Energy consumption	Active:	Eco Off: 37 dB (normal); Eco On: 35 dB (eco1) / 29 dB (eco5) Eco Off: 135 W (normal)/150 W (bright) Eco Off: 140 W (normal)/165 W (bright) Eco On: 120 W (eco1)/70 W (eco5) Eco On: 130 W (eco1)/75 W (eco5)
Computer compatibility	Standby:	0,23 W
Included with product	Max. resolution (compressed):	UXGA (1,600 x 1,200 pixels)
General	Dimensions (W x H x D):	Mains cable, IR remote controls (YT-150), quick guide, warranty card 270 x 89 x 270 mm
	Weight:	2,8 kg
	Casing/colour:	White
	Operating temperature:	5–35°C
	Warranty:	1. When used for less than 12 hours per day: Projector: three years. Light source: five years or 10,000 hours ¹ 2. When used continuously for more than 12 hours per day: Projector: two years. Light source: two years or 6,000 hours ¹

6109PUB-0208